



Even up by grinding
(Allowable lack of parallelism between ribs for each of shoulders should not exceed 1 mm)

MATERIAL COMOSITION OF L 50 II

C : 0.62 ÷ 0.76	Ni : 0.3 ÷ 0.77
Mn : 0.8 ÷ 1.0	V : 0.15 ÷ 0.25
Si : 0.3 ÷ 0.6	S : 0.045 Max
Cr : 1.9 ÷ 2.2	P : 0.045 Max
Mo : 0.22 ÷ 0.5	

1. HARDNESS : 350 BHN
2. TOLERANCE NOT MENTIONED IN CASTING SHOULD BE IS : 4896 CLASS II
3. SHARP EDGES SHOULD BE ROUNDED OFF
4. CASTING SHOULD BE FREE FROM BLOW HOLES, CAVITY, SLAG INCLUSION, CRACKS & OTHER HARMFUL CASTING DEFECTS











NOTE
(1) RADII WHICH ARE NOT GIVEN IN THE DRG SHOULD BE EXECUTED AS A CASTING RADII MIN 5 mm.
2 THRUST RING EXECUTION TYPE-II FOR MKM 25-3 GRINDING MILL
I & II EXECUTION TYPE

THIS DRG IS TRACED FROM POLISH DRG NO - 1M-33-233 I, ARCH NO CPP.PS. 210877.

CPP DRG NO.	POS NO.	DESCRIPTION	QTY	UNIT WT. IN KGS.	TOTAL WT.	MATERIAL	REMARKS
	7	SHEET 40X100X125	1		3.3	ST 35 ᵏˢ	
	6	HOLDIN DOWN NUT M48	2	0.91	0.362	"	
	5	SET SCREW	2	1.48	2.96		
	4	ELECT. WELD			8.06		
	3	ELECT. WELD			0.23		
	2	SPECIAL KEY	1		6.9		
	1	THRUST RING	1		2000	L 60 II	

PUB NO.	DESCRIPTION	QTY	UNIT WT	MATERIAL	G.A. DRG. NO	SC	DRG. NO
	THRUST RING					P.10	167.001(R) BM-042

CPP	BOKARO STEEL PLANT				
SHOP	CAPTIVE POWER PLANT				
UNIT	BOWL MILL				
DESCRIPTION OF DRAWING	THRUST RING (I & II Execution type)				
REVISIONS	TRACED	K.N. GHOSH		DATE	JUNE 90
	CHECKED	Z.N. ANSARI		SCALE	1:10 ; 1:5
	RECOMND				167.001(R)/ BM-042
	SUBMITTED				
	APPROVED				